


TWISTLOC

Bayonet caps

Solenoid valve



Features

- Easy to handle
- Ergonomic shaped

Benefits of TWISTLOC bayonet caps

- Concealed stay-clean bayonet fasteners fit nozzle holders on numerous different sprayer brands
- Flat spray nozzles (LU/ST/AD/ES/DF/OC) are totally integrated into bayonet cap – damage and impurification of the nozzle is prevented effectively

Bayonet cap	Description	Colour code	Order no.
incl. gasket (065.242.73.00) combines with following systems: – Lechler – Holder – Amazone – Schmotzer – Brendecke	for nozzles with 8 mm AF IDK, IDKN, IDKS, IDKT, LU, AD, ES OC, ST	<ul style="list-style-type: none"> ■ red ■ black ■ yellow ■ green ■ blue □ white ■ brown ■ grey 	<ul style="list-style-type: none"> 065.204.56.00 065.204.56.01 065.204.56.02 065.204.56.03 065.204.56.04 065.204.56.05 065.204.56.06 065.204.56.07
	for nozzles with 10 mm AF ID, IDN, IS, DF, FL	<ul style="list-style-type: none"> ■ red ■ black ■ yellow ■ green ■ blue ■ grey 	<ul style="list-style-type: none"> 065.202.56.00 065.202.56.01 065.202.56.02 065.202.56.03 065.202.56.04 065.202.53.00
Round-hole bayonet caps			
incl. gasket (065.242.73.00)	TR, ITR, hose shank FT	■ black	065.202.56.11
		■ d-grey	065.202.56.50
Shut-off cap			
incl. gasket (095.015.73.62.51)		■ beige	065.202.56.40

Solenoid valve	Description	Max. pressure	Order no.
	with eyelet connector		
	- for 1/2" pipe	8.0 bar	065.277.56.KH.00.0
	- for 3/4" pipe	8.0 bar	065.277.56.KL.00.0
	female thread M 18 x 1.5	8.0 bar	065.277.56.HB.00.0