

## Ball check valves Nozzle Strainers

Ball check valves, Nozzle strainers	Opening Pressure	Mesh size	L mm	D mm	Material	Order no.
<b>Ball check valves</b> 	0.5 bar	25 M	21.5	14.8	POM	065.266.56.00
	0.5 bar	60 M	21.5	14.8	POM	065.265.56.00
	0.5 bar	25 M	21	14.8	Brass	065.261.30.00
	0.5 bar	60 M	21	14.8	Brass	065.260.30.00
	2.5 bar	25 M	21.5	14.8	POM	065.266.56.02
	2.5 bar	60 M	21.5	14.8	POM	065.265.56.02
<b>Ball check valve (excl. strainers)</b> 	0.5 bar	-	18.5	14.8	POM	065.266.56.01
<b>Nozzle strainer</b> 	-	25 M	21.5	14.8	POM	065.256.56.00
	-	60 M	21.5	14.8	POM	065.257.56.00
	-	80 M	21.5	14.8	POM	A.424.310.5
<b>Slotted strainer</b> 	-	≅ 25 M	21.0	14.8	POM	095.009.56.13.43
<b>Cup strainer</b> 	-	25 M	8.5	14.8	Copper/Monel	065.252.26.00
	-	25 M	8.5	15.0	PA/Monel	200.029.26.00.03
	-	60 M	8.5	15.0	PA/Stainl. steel	200.029.1C.01.03